

..... ACCESSORIES





SPLIT-LOCK +

FEATURES



- No special tools required
- Reusable – can install with cable inside
- Heat, UV stabilized
- Fungus and chemical resistant
- Air and water tight
- No I.D. reduction
- Not recommended for plow chute
- Meets UL 514B pullout requirements
- ETL listed to UL STD 514B and CSA STD C22.2 18.3
- Made in the USA

The Split Lock + is a split coupler produced from a glass fiber reinforced nylon resin. The coupler is heat and UV stabilized, and offers excellent impact strength. It's reusable and is ideal for temporarily coupling conduits, particularly at slack-loop locations, and also for air-assisted jetting applications. The coupler is easily assembled using a 7/16" nut driver.

PART NUMBER	DESCRIPTION	PACKAGING (CS)	SHIP WEIGHT (LBS)
20003907	Split-Lock + Coupler 1.00" SDR 	10	5.5
20003908	Split-Lock + Coupler 1.25" SDR 	10	5.5
20003909	Split-Lock + Coupler 1.50" SDR 	10	6
20003910	Split-Lock + Coupler 2.00" SDR 	10	6



The Palm Ratchet comes with 5/16" and 7/16" sockets and is used with Split-Lock + Couplers.

PART NUMBER	DESCRIPTION	PACKAGING	SHIP WEIGHT
20002747	Palm Ratchet with 5/16" and 7/16" sockets	each	1

DL_SPLIT-LOCK+_09.2018